



(الوزن (كجم) الحد من السرعة (رتمين (KN تصنيف الحمل الأساسي (الأبعاد الحدودية (مم تحمل التسميات

	د	د	ب	كور	سجل تجاري	زيت	شحم	
719/8	8	19	6	2.5	1.5	75000	120000	0.01
71900	10	22	6	2.9	1.8	70000	110000	0.01
71901	12	24	6	3.2	2.2	63000	95000	0.01
71902	15	28	7	4.8	3.4	53000	80000	0.02
71903	17	30	7	5.1	3.8	50000	75000	0.02
71904	20	37	9	7.4	5.8	40000	60000	0.04
71905	25	42	9	7.6	6.5	34000	50000	0.04
71906	30	47	9	8	7.6	30000	45000	0.05
71907	35	55	10	11	10.9	26000	40000	0.07
71908	40	62	12	14	14.2	20000	34000	0.11
71909	45	68	12	14.7	16.1	18000	30000	0.13
71910	50	72	12	19	21.2	17000	28000	0.13
71911	55	80	13	23.7	27.4	15000	24000	0.18
71912	60	85	13	24.8	30.3	14000	22000	0.19
71913	65	90	13	25.1	31.9	13000	20000	0.2
71914	70	100	16	34.5	43.4	12000	19000	0.33
71915	75	105	16	25	45.6	11000	18000	0.35
71916	80	110	16	35.5	47.8	10000	17000	0.37
71917	85	120	18	46.5	61.9	9500	16000	0.53
71918	90	125	18	47.2	64.8	9000	15000	0.56
71919	95	130	18	47.8	67.8	9000	15000	0.58



Thin-wall angular contact ball bearings 719 series

71920	100	140	20	60.4	84.4	8500	14000	0.79
71921	105	145	20	61.4	88.2	8000	13000	0.83
71922	110	150	20	62	91.9	7500	12000	0.86
71924	120	16F	22	73.7	107.6	7000	11000	1.17
71926	130	180	24	76	117.1	6700	10000	1.58
71928	140	190	24	78.9	126.4	6000	9000	1.68
71930	150	210	28	118.2	175.1	5600	8500	2.48